## **98/589838**IAP11 Rec'd PCT/PTO 17 AUG 2006

## **Amendments to the Claims**

- 1. (Currently Amended) Antenna for wireless communication devices, comprising
- a) a dielectric substrate (1)-with two pairs of metallic resonator structures (2, 3) provided on its surface (4),
- b) each pair of resonator structures (2, 3) comprising a first resonator structure (2A, 3A) connected to a feed line (2C, 3C), and a second resonator structure (2B, 3B) having a connection to ground (5, 5), the first and the second resonator structure being electrically isolated from each other and being arranged adjacent to each other.
- 2. (Original) Antenna according to claim 1, characterized in that the first and second resonator structures are elongated structures.
- 3. (Currently Amended) Antenna according to claim 1, characterized in that the antenna has a single connection to ground which branches into the second resonator structures (2B, 3B).
- 4. (Original) Antenna according to claim 2, characterized in that the length of the second resonator structures measured from the point of branching is different.
- 5. (Currently Amended) Antenna according to claim 1, characterized in that at least one of the first or second resonator structures is connected to one ore more passive components (6, 6).
- 6. (Original) Antenna according to claim 1, characterized in that the first pair of resonator structures has a resonance frequency substantially in a frequency range of 824 MHz to 960 MHz.
- 7. (Original) Antenna according to claim 1, characterized in that the second pair of resonator structures has a resonance frequency substantially in a frequency range of 1710 MHz to 1990 MHz.

Appl. No. Unassigned; Docket No. AT04 0009US1 Amdt. dated August 17, 2006 Preliminary Amendment

- 8. (Original) Mobile communication device, characterized in that the mobile communication device comprises an antenna according to claim 1.
- 9. (Original) Mobile communication device according to claim 8, characterized in that the mobile communication device being designed as a transponder for radio frequency identification (RFID) purposes.